

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : C10L 1/02, 1/14	A1	(11) International Publication Number: WO 94/10267 (43) International Publication Date: 11 May 1994 (11.05.94)
(21) International Application Number: PCT/EP93/02908 (22) International Filing Date: 21 October 1993 (21.10.93) (30) Priority data: 9222458.3 26 October 1992 (26.10.92) GB (71) Applicant (for all designated States except US): EXXON CHEMICAL PATENTS INC. [US/US]; 1900 East Linden Avenue, Linden, NJ 07036 (US). (72) Inventors; and (75) Inventors/Applicants (for US only) : DAVIES, Brian, William [GB/GB]; Pound Furlong, London Road, Blewbury, Oxfordshire OX11 9PD (GB). LEWTAS, Kenneth [GB/US]; 1130 Minisink Way, Westfield, NJ 07090 (US). LOMBARDI, Alessandro [IT/GB]; 2 The Ride, Tubney Wood, Abingdon, Oxfordshire OX13 5QF (US).		(74) Agents: MANSELL, Keith, Rodney et al.; Exxon Chemical Limited, Exxon Chemical Technology Centre, P.O. Box 1, Abingdon, Oxfordshire OX13 6BB (GB). (81) Designated States: AU, BR, CA, FI, JP, KR, NO, RU, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: OIL ADDITIVES AND COMPOSITIONS (57) Abstract The low temperature properties of a blend of biofuel and petroleum-based fuel oil are improved by the addition of an ethylene-unsaturated ester copolymer, or a comb polymer, or a polar N compound, or a compound having at least one linear alkyl group connected to a non-polymeric organic residue.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TC	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

- 1 -

"Oil Additives and Compositions"

5 This invention relates to oil compositions, primarily to fuel oil compositions, and more especially to fuel oil compositions susceptible to wax formation at low temperatures, and to additive compositions for such fuel oil compositions.

10 Fuel oils, whether derived from petroleum or from vegetable sources, contain components that at low temperature tend to precipitate as large crystals of wax in such a way as to form a gel structure which causes the fuel to lose its ability to flow. The lowest temperature at which the fuel will still flow is known as the pour point.

15 As the temperature of the fuel falls and approaches the pour point, difficulties arise in transporting the fuel through lines and pumps. Further, the wax crystals tend to plug fuel lines, screens, and filters at temperatures above the pour point. These problems are well recognized in the art, and various
20 additives have been proposed, many of which are in commercial use, for depressing the pour point of fuel oils. Similarly, other additives have been proposed and are in commercial use for reducing the size and changing the shape of the wax crystals that do form. Smaller size crystals are desirable since they are less
25 likely to clog a filter. The wax from a diesel fuel, which is primarily an alkane wax, crystallizes as platelets; certain additives inhibit this, causing the wax to adopt an acicular habit, the resulting needles being more likely to pass through a filter than are platelets. The additives may also have the effect of
30 retaining in suspension in the fuel the crystals that have formed, the resulting reduced settling also assisting in prevention of blockages.

 Fuels from vegetable sources, also known as biofuels, are believed to be less damaging to the environment on
35 combustion, and are obtained from a renewable resource. It has been reported that on combustion less carbon dioxide is formed

- 2 -

than is formed by the equivalent quantity of petroleum distillate fuel, e.g., diesel fuel, and very little sulphur dioxide is formed. Certain derivatives of vegetable oil, for example rapeseed oil, e.g., those obtained by saponification and re-esterification with
5 a monohydric alcohol, may be used as a substitute for diesel fuel. It has recently been reported that mixtures of a rapeseed ester, for example, rapeseed methyl ester (RME), with petroleum distillate fuels in ratios of, for example, 10:90 by volume are likely to be commercially available in the near future.

10 However, such mixtures may have poorer low temperature flow properties than the individual components themselves. A measure of the flowability of fuels at low temperature is the cold filter plugging point (CFPP) test, described in "Journal of the Institute of Petroleum" 52(1966),
15 173 to 185. In one case, described in more detail below, a mixture of equal volumes of a diesel fuel with a CFPP of -6°C and an RME with a CFPP of -13°C had a CFPP of only -5°C, while a 90:10 diesel:RME mixture had a CFPP of -4°C, both higher than the CFPP of either fuel alone.

20 A further problem encountered at temperatures low enough for wax to form in a fuel is the settlement of the wax to the lower region of any storage vessel. This has two effects: one in the vessel itself where the settled layer of wax may block an outlet at the lower end, and the second in subsequent use of the
25 fuel. The composition of the wax-rich portion of fuel will differ from that of the remainder, and will have poorer low temperature properties than that of the homogeneous fuel from which it is derived.

30 There are various additives available which change the nature of the wax formed, so that it remains suspended in the fuel, achieving a dispersion of waxy material throughout the depth of the fuel in the vessel, with a greater or lesser degree of uniformity depending on the effectiveness of the additive on the fuel.

- 3 -

Although the way in which CFPP depressants and wax anti-settling additives function is not completely understood, there is evidence that their effectiveness depends to a significant extent on matching of the alkanes in the fuel to alkyl or alkylene chains in the additive, the growth of the alkane wax crystals being affected, for example, by the co-crystallization of an alkyl chain of similar length in an additive.

Whereas the aliphatic middle distillate fuels contain largely alkanes, however, the aliphatic moieties of biofuels contain a high proportion of unsaturated chains. For example, rapeseed oil typically contains the esters of, in addition to some 11 to 19% C₁₆ to C₁₈ saturated acids, some 23 to 32% mono-, 40 to 50% di- and 4 to 12 triunsaturated C₁₈ to C₂₂ acids, primarily oleic, linoleic, linolenic, and erucic acids. These do not crystallize in the same way as do the saturated materials, and it would therefore not be expected that the additives suitable for improving low temperature properties of petroleum-based fuels would be effective in biofuels, and that their effectiveness in mixtures of biofuels and petroleum-based fuels would be limited in accordance with the proportion of petroleum fuel in the mixture.

It has surprisingly been found, however, that certain cold flow additives have a beneficial effect on low temperature properties of a biofuel-petroleum fuel mixture greater than in the petroleum fuel alone.

The present invention provides a fuel oil composition comprising a biofuel, a petroleum-based fuel oil, and an additive comprising at least one petroleum fuel oil wax crystal modifier or pour point depressant or both, comprising (a) an oil-soluble copolymer of ethylene or (b) a comb polymer or, (c) a polar nitrogen compound, or (d) a compound in which at least one substantially linear alkyl group having 10 to 30 carbon atoms is connected to a non-polymeric organic residue to provide at least one linear chain of atoms that includes the carbon atoms of said

- 4 -

alkyl groups and one or more non-terminal oxygen atoms, or (e) one or more of components (a), (b), (c) and (d).

As biofuel, or fuel derived from a vegetable source, especially an agricultural product, there may be used, for example, a liquid fuel, especially an oil. A preferred oil is a vegetable oil, for example soya, palm, sunflower, cottonseed, peanut, coconut or rapeseed oil, either as such or, preferably, saponified and esterified (or transesterified), preferably with a monohydric alcohol, especially methanol. The presently preferred biofuel is rapeseed methyl ester.

The petroleum-based fuel oil may be a distillate, especially a middle distillate, petroleum fraction. Such distillate fuel oils generally boil within the range of from 100°C to 500°C, e.g. 150° to 400°C. The fuel oil may comprise atmospheric distillate or vacuum distillate, or cracked gas oil or a blend in any proportion of straight run and thermally and/or catalytically cracked distillates. The most common petroleum distillate fuels are kerosene, jet fuels, diesel fuels, heating oils and heavy fuel oils. The heating oil may be a straight atmospheric distillate, or it may contain vacuum gas oil or cracked components or both.

The invention is applicable to mixtures of the fuels in all proportions; more especially, however, the composition comprises from 5 to 75%, more especially 10 to 50%, of biofuel. It is within the scope of the invention to use two or more petroleum-based fuels or, more especially, two or more biofuels, in admixture with one or more of the other type of fuel.

Preferably, the mixture of the fuels of this invention contains less than 5% by volume of methanol, for example 4%, 3%, 2% or 1% or substantially no methanol.

The components of the additive will now be discussed in further detail as follows. It should be noted that individual polymers or compounds may fall within more than one of the definitions of (a), (b), (c) and (d) herein.

35

- 5 -

(a) Oil Soluble Copolymers of Ethylene

The oil-soluble copolymer, component (a), may be a copolymer of ethylene with an ethylenically unsaturated ester, such as a copolymer of ethylene with an ester of an unsaturated carboxylic acid and a saturated alcohol, but the ester is preferably one of an unsaturated alcohol with a saturated carboxylic acid. An ethylene-vinyl ester copolymer is advantageous; an ethylene-vinyl acetate, ethylene-vinyl propionate ethyl-vinyl hexanoate, or ethyl-vinyl octanoate copolymer is preferred.

More especially, component (a) may comprise an ethylene copolymer having, in addition to units derived from ethylene, units of the formula



wherein R represents H or CH₃, and R³⁰ represents a group of the formula COOR³ or OOCR⁴, wherein R³ and R⁴ independently represent a hydrocarbonyl group.

As described in U.S. Patent No. 3,961,916, a composition comprising both a wax growth arrestor and a nucleating agent is an effective low temperature flow improver for middle distillate fuel oils. The arrestor and nucleating agent are preferably a lower molecular weight ethylene-unsaturated ester polymer with a higher ester content, and a higher molecular weight ethylene-unsaturated ester polymer with a lower ester content respectively. Advantageously the ester is vinyl acetate in both copolymers. Such a combination has been found extremely effective in the present invention. More especially, the combination comprises:

30 (i) an oil-soluble ethylene copolymer having, in addition to units derived from ethylene, from 7.5 to 35 molar per cent of units of the formula



and

- 6 -

(ii) an oil-soluble ethylene copolymer having, in addition to units derived from ethylene, up to 10 molar per cent of units of the formula



5 wherein each R independently represents H or CH₃, and each R¹, and R² independently represents a group of the formula COOR³ or OOCR⁴, wherein R³ and R⁴ independently represent a hydrocarbyl group, the proportion of units I in polymer (i) being at least 2 molar percent greater than the proportion of units II in polymer
10 (ii).

As used in this specification the term "hydrocarbyl" refers to a group having a carbon atom directly attached to the rest of the molecule and having a hydrocarbon or predominantly hydrocarbon character. Among these, there may be mentioned
15 hydrocarbon groups, including aliphatic, (e.g., alkyl or alkenyl), alicyclic (e.g., cycloalkyl or cycloalkenyl), aromatic, aliphatic and alicyclic-substituted aromatic, and aromatic-substituted aliphatic and alicyclic groups. Aliphatic groups are advantageously saturated. These groups may contain non-
20 hydrocarbon substituents provided their presence does not alter the predominantly hydrocarbon character of the group. Examples include keto, halo, hydroxy, nitro, cyano, alkoxy and acyl. If the hydrocarbyl group is substituted, a single (mono) substituent is preferred. Examples of substituted hydrocarbyl groups include
25 2-hydroxyethyl, 3-hydroxypropyl, 4-hydroxybutyl, 2-ketopropyl, ethoxyethyl, and propoxypropyl. The groups may also or alternatively contain atoms other than carbon in a chain or ring otherwise composed of carbon atoms. Suitable hetero atoms include, for example, nitrogen, sulphur, and, preferably, oxygen.
30 Advantageously, the hydrocarbyl group contains at most 30, preferably at most 15, more preferably at most 10 and most preferably at most 8, carbon atoms.

In respect of formulae X, I and II above, advantageously, R represents H and advantageously, R³ and R⁴ each independently
35 represents an alkenyl or as indicated above, preferably, an alkyl

- 7 -

group, which is advantageously linear. If the alkyl or alkenyl group is branched, for example, as in the 2-ethylhexyl group, the alpha-carbon atom is advantageously part of a methylene group. Advantageously, the alkyl or alkenyl group contains up to 30 carbon atoms, preferably from 1 (2 in the case of alkenyl) to 14 carbon atoms, and more preferably from 1 to 10 carbon atoms. As examples of alkyl or alkenyl groups there may be mentioned methyl, ethyl, propyl, n-butyl, iso-butyl, and isomers, preferably the linear isomers, of pentyl, hexyl, heptyl, octyl, nonyl, decyl, undecyl, dodecyl, tridecyl, tetradecyl, pentadecyl, hexadecyl, heptadecyl, octadecyl, nonadecyl and icosyl, and their corresponding alkenyl, advantageously alk-omega-enyl, radicals.

As cycloalkyl, alkaryl and aryl radicals, there may be mentioned, for example, cyclohexyl, benzyl and phenyl.

The copolymer or copolymers may also contain units of formulae other than those mentioned above, for example units of the formula



where R^5 represents -OH, or of the formula



where R^6 and R^7 each independently represent hydrogen or an alkyl group with up to 6 carbon atoms, the units IV advantageously being derived from isobutylene, diisobutylene, 2-methylbut-2-ene or 2-methylpent-2-ene.

Units of the formula X, I or II or may be terminal units but are advantageously internal units. Advantageously, units of the formula I represent from 10 to 25, preferably from 10 to 20, and more preferably from 11 to 16, mole per cent of the polymer (i). Advantageously, units of the formula II represent up to 7.5, preferably from 0.3 to 7.5, and more preferably from 3.5 to 7.0, mole per cent of the polymer (ii).

In the copolymer having units of the formula X as defined above, units of the formula X preferably represent from 5 to 40 mole per cent of the copolymer, more preferably from 7.5 to 35 mole per cent, most preferably 7.5 to 25 mole per cent. Such

- 8 -

copolymer advantageously has a number average molecular weight, as measured by gel permeation chromatography, of at most 14,000, preferably 2,000 to 5,500, and most preferably 3,000 to 4,000.

- 5 The copolymer (i) advantageously has a number average molecular weight, as measured by gel permeation chromatography, of at most 14,000, advantageously at most 10,000, more advantageously in the range of 1,400 to 7,000, preferably 2,000 to 5,500 and most preferably about 4,000. For
- 10 the polymer (ii) the number average molecular weight is advantageously at most 20,000, preferably up to 15,000 and more preferably from 1,200 to 10,000, and most preferably from 3,000 to 10,000. The preferred number average molecular weight will depend to some extent on the number of carbon
- 15 atoms in R^3 and R^4 , the higher that number the higher the preferred molecular weight within the range above. Advantageously, the number average molecular weight of the polymer (ii) is greater, by at least 500, and preferably at least 1,000, than that of polymer (i).
- 20 Polymers in which R^1 or R^2 represents $OOCH^4$ are preferred and more preferably both R^1 and R^2 both represent $OOCH^4$.

Polymers containing units I and units II are advantageously present in a weight ratio of from 10:1 to 1:10, preferably from 10:1 to 1:3, and more preferably from 7:1 to 1:1.

25 It is within the scope of the invention to use two or more polymers (i) and/or two or more polymers (ii) in the same additive composition. It is also within the scope of the invention to employ a polymer (i) or (ii) having two or more

30 different units of types I and II. Units I in polymer (i) may be the same as or different from units II in polymer (ii).

The oil-soluble copolymer of ethylene may also comprise a copolymer of ethylene and at least one α -olefin, having a number average molecular weight of at least 30,000. Preferably

35 the α -olefin has at most 20 carbon atoms. Examples of such

- 9 -

olefins are propylene, 1-butene, isobutene, n-octene-1, isooctene-1, n-decene-1, and n-dodecene-1. The copolymer may also comprise small amounts, e.g, up to 10% by weight, of other copolymerizable monomers, for example olefins other than α -olefins, and non-conjugated dienes. The preferred copolymer is an ethylene-propylene copolymer. It is within the scope of the invention to include two or more different ethylene- α -olefin copolymers of this type.

The number average molecular weight of the ethylene- α -olefin copolymer is, as indicated above, at least 30,000, as measured by gel permeation chromatography (GPC) relative to polystyrene standards, advantageously at least 60,000 and preferably at least 80,000. Functionally no upper limit arises but difficulties of mixing result from increased viscosity at molecular weights above about 150,000, and preferred molecular weight ranges are from 60,000 and 80,000 to 120,000.

Advantageously, the copolymer has a molar ethylene content between 50 and 85 per cent. More advantageously, the ethylene content is within the range of from 57 to 80%, and preferably it is in the range from 58 to 73%; more preferably from 62 to 71%, and most preferably 65 to 70%.

Preferred ethylene- α -olefin copolymers are ethylene-propylene copolymers with a molar ethylene content of from 62 to 71% and a number average molecular weight in the range 60,000 to 120,000, especially preferred copolymers are ethylene-propylene copolymers with an ethylene content of from 62 to 71% and a molecular weight from 80,000 to 100,000.

The copolymers may be prepared by any of the methods known in the art, for example using a Ziegler type catalyst. The polymers should be substantially amorphous, since highly crystalline polymers are relatively insoluble in fuel oil at low temperatures.

The composition may also comprise a further ethylene- α -olefin copolymer, advantageously with a number average molecular weight of at most 7500, advantageously from 1,000 to

- 10 -

6,000, and preferably from 2,000 to 5,000, as measured by vapour phase osmometry. Appropriate α -olefins are as given above, or styrene, with propylene again being preferred. Advantageously the ethylene content is from 60 to 77 molar per cent although for ethylene-propylene copolymers up to 86 molar per cent by weight ethylene may be employed with advantage.

The copolymer should preferably be soluble in the oil to the extent of at least 1000 ppm by weight per weight of oil at ambient temperature. However, at least some of the copolymer may come out of solution near the cloud point of the oil and function to modify the wax crystals that form.

The composition advantageously contains the ethylene copolymer, or copolymer combination, in a total proportion of 0.0005% to 1%, advantageously 0.001 to 0.5%, and preferably 0.01 to 0.15% by weight, based on the weight of fuel.

(b) Comb Polymers


Component (b) is a comb polymer. Such polymers are discussed in "Comb-Like Polymers. Structure and Properties", N. A. Platé and V. P. Shibaev, J. Poly. Sci. Macromolecular Revs., 8, p 117 to 253 (1974).

Generally, comb polymers have one or more long chain branches such as hydrocarbyl branches having from 10 to 30 carbon atoms, pendant from a polymer backbone, said branch or branches being bonded directly or indirectly to the backbone. Examples of indirect bonding include bonding via interposed atoms or groups, which bonding can include covalent and/or electrovalent bonding such as in a salt.

Advantageously, the comb polymer is a homopolymer having, or a copolymer at least 25 and preferably at least 40, more preferably at least 50, molar per cent of the units of which have, side chains containing at least 6, and preferably at least 10, atoms, selected from for example carbon, nitrogen and oxygen, in a linear chain.

- 11 -

As examples of preferred comb polymers there may be mentioned those containing units of the general formula



5

wherein D = R¹¹, COOR¹¹, OCOR¹¹, R¹²COOR¹¹, or OR¹¹,

E = H, CH₃, D, or R¹²,

G = H or D

J = H, R¹², R¹²COOR¹¹, or an aryl or heterocyclic

10 group,

K = H, COOR¹², OCOR¹², OR¹², or COOH,

L = H, R¹², COOR¹², OCOR¹², COOH, or aryl,

R¹¹ ≥ C₁₀ hydrocarbyl,

R¹² ≥ C₁ hydrocarbyl,

15 and m and n represent mole ratios, m being within the range of from 1.0 to 0.4, n being in the range of from 0 to 0.6. R¹¹ advantageously represents a hydrocarbyl group with from 10 to 30 carbon atoms, while R¹² advantageously represents a hydrocarbyl group with from 1 to 30 carbon atoms.

20 The comb polymer may contain units derived from other monomers if desired or required. It is within the scope of the invention to include two or more different comb polymers.

The molecular weight of the comb polymer is not critical. Advantageously, however, it is within the range of from 25 1,000 to 100,000, preferably between 1,000 and 30,000, as measured by vapour phase osmometry.

These comb polymers may be copolymers of maleic anhydride or fumaric acid and another ethylenically unsaturated

- 12 -

monomer, e.g., an alpha-olefin or an unsaturated ester, for example, vinyl acetate. It is preferred but not essential that equimolar amounts of the comonomers be used although molar proportions in the range of 2 to 1 and 1 to 2 are suitable.

- 5 Examples of olefins that may be copolymerized with e.g., maleic anhydride, include 1-decene, 1-dodecene, 1-tetradecene, 1-hexadecene, and 1-octadecene.

- The copolymer may be derivatized, e.g., esterified, by any suitable technique, e.g., by reaction with alcohols, primary or
10 secondary amines, or amino-alcohols, and although preferred it is not essential that the maleic anhydride or fumaric acid be at least 50% derivatized. Examples of alcohols which may be used include n-decan-1-ol, n-dodecan-1-ol, n-tetradecan-1-ol, n-hexadecan-1-ol, and n-octadecan-1-ol. The alcohols may also
15 include up to one methyl branch per chain, for example, 1-methylpentadecan-1-ol, 2-methyltridecan-1-ol. The alcohol may be a mixture of normal and single methyl branched alcohols. It is preferred to use pure alcohols rather than the commercially available alcohol mixtures but if mixtures are used the R^{12}
20 refers to the average number of carbon atoms in the alkyl group; if alcohols that contain a branch at the 1 or 2 positions are used R^{12} refers to the straight chain backbone segment of the alcohol.

- These comb polymers may especially be fumarate or itaconate polymers and copolymers such for example as those
25 described in EP-A-153176, -153177, -155807, -156577 and -225688, and WO 91/16407.

- Particularly preferred fumarate comb polymers are copolymers of alkyl fumarates and vinyl acetate, in which the alkyl groups have from 12 to 20 carbon atoms, more especially
30 polymers in which the alkyl groups have 12 carbon atoms or in which the alkyl groups are a mixture of C_{12}/C_{14} alkyl groups, made, for example, by solution copolymerizing an equimolar mixture of fumaric acid and vinyl acetate and reacting the resulting copolymer with the alcohol or mixture of alcohols,
35 which are preferably straight chain alcohols. When the mixture

- 13 -

is used it is advantageously a 1:1 by weight mixture of normal C₁₂ and C₁₄ alcohols. Furthermore, mixtures of the C₁₂ ester with the mixed C₁₂/C₁₄ ester may advantageously be used. In such mixtures, the ratio of C₁₂ to C₁₂/C₁₄ is advantageously in
5 the range of from 1:1 to 4:1, preferably 2:1 to 7:2, and most preferably about 3:1, by weight.

Other suitable comb polymers are the polymers and copolymers of α -olefins and esterified copolymers of styrene and maleic anhydride, and esterified copolymers of styrene and
10 fumaric acid; mixtures of two or more comb polymers may be used in accordance with the invention and, as indicated above, such use may be advantageous.

The composition advantageously contains the comb polymer in a proportion of 0.0005 to 1, preferably from 0.001 to
15 0.5, and most preferably from 0.01 to 0.15, per cent by weight based on the weight of the fuel.

(c) Polar Nitrogen Compounds

20 For example, there may be used one or more of the compounds (i) to (iii) as follows:

(i) An amine salt and/or amide obtainable by treating at least one molar proportion of a hydrocarbyl amine with a molar proportion of a hydrocarbyl mono- or poly-carboxylic acid, e.g.,
25 having 1 to 4 carboxylic acid groups, or with an anhydride of such an acid.

Ester/amides may be used containing from 30 to 300, preferably 50 to 150 total carbon atoms. These nitrogen compounds are described in US Patent No. 4,211,534. Suitable
30 amines are usually long chain C₁₂ to C₄₀ primary, secondary, tertiary or quaternary amines or mixtures thereof but shorter chain amines may be used provided the resulting nitrogen compound is oil soluble and accordingly normally contains from 30 to 300 total carbon atoms. The nitrogen compound preferably

- 14 -

contains at least one straight chain C₈ to C₄₀, preferably C₁₄ to C₂₄, alkyl segment.

- Suitable amines include primary, secondary, tertiary or quaternary, but preferably are secondary. Tertiary and quaternary amines form only amine salts. Examples of amines include tetradecyl amine, cocoamine, and hydrogenated tallow amine. Examples of secondary amides include dioctadecyl amine and methyl-behenyl amine.
- 10 Amine mixtures are also suitable, for example, those derived from natural materials. A preferred secondary amine is di(hydrogenated tallow) amine having alkyl groups derived from hydrogenated tallow fat composed of approximately 4% C₁₄, 31% C₁₆ and 59% C₁₈ radicals.
- 15 Examples of suitable carboxylic acids and their anhydrides for preparing the nitrogen compounds include cyclohexane-1,2-dicarboxylic acid, cyclohexene-1,2-dicarboxylic acid, cyclopentane-1,2-dicarboxylic acid and naphthalene dicarboxylic acid, and 1,4-dicarboxylic acids including dialkyl spirobis lactone. Generally, these acids have from 5 to 13 carbon atoms in the cyclic moiety. Preferred acids are benzene dicarboxylic acids such as phthalic acid, isophthalic acid, and terephthalic acid. Phthalic acid or its anhydride is particularly preferred.
- 20 The preferred compounds are an amide-amine salt of phthalic anhydride with two molar proportions of hydrogenated tallow amine, the diamide product obtainable by dehydrating this salt, and the amide-amine salt of ortho-sulphobenzoic anhydride and hydrogenated tallow amine.
- 25 Other examples are long chain alkyl or alkylene substituted dicarboxylic acid derivatives, for example, amine salts or monoamides of substituted succinic acids, examples of which are described in, for example, U.S. Patent No. 4,147,520. Suitable amines may be those described above. Further examples
- 30

- 15 -

are condensates such, for example, as described in EP-A-327,423, EP-A-413,279 and EP-A-398,101.

- (ii) A compound comprising or including a ring system, the compound carrying on the ring system at least two but preferably only two substituents of the general formula



where A is an aliphatic hydrocarbyl group that is optionally interrupted by one or more hetero atoms and that is straight chain or branched, and R^{21} and R^{22} are the same or different and each is independently a hydrocarbyl group containing 9 to 40 carbon atoms optionally interrupted by one or more hetero atoms, the substituents being the same or different and the compound optionally being in the form of a salt thereof, for example the acetate or the hydrochloride.

- Preferably, A has from 1 to 20 carbon atoms and is preferably a methylene or polymethylene group.

The cyclic ring system may be a homocyclic, heterocyclic, monocyclic, polycyclic or fused polycyclic assembly, or a system where two or more such cyclic assemblies are joined to one another and in which the cyclic assemblies may be the same or different. Where there are two or more such cyclic assemblies, the defined substituents may be on the same or different assemblies, preferably on the same assembly. Preferably, the or each cyclic assembly is aromatic, more preferably a benzene ring. Most preferably, the cyclic ring system is a single benzene ring, the substituents preferably being in the ortho or meta positions, which benzene ring may be optionally further substituted.

- The ring atoms in the cyclic assembly or assemblies are preferably carbon atoms but may for example include one or more ring N, S or O atoms.

Examples of such polycyclic assemblies include:

- (a) condensed benzene structures, for example, naphthalene, anthracene, phenanthrene, and pyrene;

- 16 -

- (b) condensed ring structures where none of or not all of the rings is or are benzene, for example, azulene, indene, hydroindene, fluorene, and diphenyleneoxide;
- (c) rings joined "end-on", for example, diphenyl;
- 5 (d) heterocyclic compounds, for example, quinoline, indole, 2,3-dihydroindole, benzofuran, coumarin, isocoumarin, benzothiophene, carbazole and thiodiphenylamine;
- (e) non-aromatic or partially saturated ring systems, for example, decalin (decahydronaphthalene), alpha-pinene, cardinene, and bornylene; and
- 10 (f) multi-ring structures, for example, norbornene, bicycloheptane (norbornane), bicyclooctane, and bicyclooctene.

15 Each hydrocarbyl group R²¹ and R²² may for example be an alkylene or alkylene group or a mono- or polyalkoxyalkyl group. Preferably, each hydrocarbyl group is a linear alkylene group. The number of carbon atoms in each hydrocarbyl group is preferably from 16 to 40, more preferably 16 to 24.

20 The compounds may conveniently be made by reducing the corresponding amide which may in turn have been made by reaction of a secondary amine and the appropriate acid chloride.

(iii) A condensate of a long chain primary or secondary amine with a carboxylic acid-containing polymer.

25 Specific examples include polymers such, for example, as described in GB-A-2,121,807, FR-A-2,535,723 and DE-A-3,941,561; and also esters of telomer acid and alkanoloamines such, for example, as described in U.S. Patent No. 4,639,256; and the reaction product of an amine containing a
30 branched carboxylic acid ester, an epoxide and a mono-carboxylic acid polyester such, for example, as described in U.S. Patent No. 4,631,071.

Compositions comprising at least one comb polymer and/or at least one polar nitrogen compound in addition to an

- 17 -

ethylene/ unsaturated ester copolymer have much improved resistance to wax settlement and are preferred.

(d) Compounds as Defined Herein

5

By "substantially linear" is meant that the alkyl group is preferably straight chain, but that essentially straight chain alkyl groups having a small degree of branching such as in the form of a single methyl group may be used.

10

Preferably, the compound has at least two of said alkyl groups when the linear chain may include the carbon atoms of more than one of said alkyl groups. When the compound has at least three of said alkyl groups, there may be more than one of such linear chains, which chains may overlap. The linear chain or chains may provide part of a linking group between any two such alkyl groups in the compound.

15

The oxygen atom or atoms are preferably directly interposed between carbon atoms in the chain and may, for example, be provided in the form of a mono- or poly-oxyalkylene group, said oxyalkylene group preferably having 2 to 4 carbon atoms, examples being oxyethylene and oxypropylene.

20

As indicated the chain or chains include carbon and oxygen atoms. They may also include other hetero-atoms such as nitrogen atoms.

25

The compound may be an ester where the alkyl groups are connected to the remainder of the compound as -O-CO-n-alkyl, or -CO-O-n-alkyl groups, in the former the alkyl groups being derived from an acid and the remainder of the compound being derived from a polyhydric alcohol and in the latter the alkyl groups being derived from an alcohol and the remainder of the compound being derived from a polycarboxylic acid. Also, the

30

35

- 18 -

compound may be an ether where the alkyl groups are connected to the remainder of the compound as —O—n—alkyl groups. The compound may be both an ester and an ether or it may contain different ester groups.

5

Examples include polyoxyalkylene esters, ethers, ester/ethers and mixtures thereof, particularly those containing at least one, preferably at least two, C₁₀ to C₃₀ linear alkyl groups and a polyoxyalkylene glycol group of molecular weight up to 5,000, preferably 200 to 5,000, the alkylene group in said polyoxyalkylene glycol containing from 1 to 4 carbon atoms, as described in EP-A-61 895 and in U.S. Patent No. 4,491,455.

The preferred esters, ethers or ester/ethers which may be used may be structurally depicted by the formula

15



where R²³ and R²⁴ are the same or different and may be

- (a) n-alkyl-
- (b) n-alkyl-CO-
- (c) n-alkyl-OCO-(CH₂)_n-
- (d) n-alkyl-OCO-(CH₂)_nCO-

20

n being, for example, 1 to 34, the alkyl group being linear and containing from 10 to 30 carbon atoms, and B representing the polyalkylene segment of the glycol in which the alkylene group has from 1 to 4 carbon atoms, for example, polyoxymethylene, polyoxyethylene or polyoxytrimethylene moiety which is substantially linear; some degree of branching with lower alkyl side chains (such as in polyoxypropylene glycol) may be tolerated but it is preferred that the glycol should be substantially linear. B may also contain nitrogen.

25

Suitable glycols generally are substantially linear polyethylene glycols (PEG) and polypropylene glycols (PPG) having a molecular weight of about 100 to 5,000, preferable about 200 to 2,000. Esters are preferred and fatty acids containing from 10 to 30 carbon atoms are useful for reacting with the glycols to form the ester additives, it being preferred

30

35

- 19 -

to use a C₁₈ to C₂₄ fatty acid, especially behenic acid. The esters may also be prepared by esterifying polyethoxylated fatty acids or polyethoxylated alcohols.

Polyoxyalkylene diesters, diethers, ether/esters and mixtures thereof are suitable as additives, diesters being preferred when the petroleum based component is a narrow boiling distillate, when minor amounts of monoethers and monoesters (which are often formed in the manufacturing process) may also be present. It is important for active performance that a major amount of the dialkyl compound is present. In particular, stearic or behenic diesters of polyethylene glycol, polypropylene glycol or polyethylene/polypropylene glycol mixtures are preferred.

Examples of other compounds in this general category are those described in Japanese Patent Publication Nos. 2-51477 and 3-34790, and EP-A-117,108 and EP-A-326,356, and cyclic esterified ethoxylates such as described EP-A-356,256.

The composition may contain other additives for improving low temperature and/or other properties, many of which are in use in the art or known from the literature.

The invention also provides an additive concentrate comprising the additive in admixture with a biofuel or with a mixture of a biofuel and a petroleum-based fuel oil. The invention further provides the use of the additive to improve the low temperature properties of a biofuel/petroleum-based fuel mixture.

The following Examples, in which all parts and percentages are by weight, number average molecular weights are measured by vapour phase osmometry, and internal methyl groups in polymers by proton NMR (i.e., excluding terminal methyl groups and those arising from acetate groups), illustrate the invention.

The petroleum-based fuels used in the Examples had the following characteristics.

35

- 20 -

	Fuel 1	Fuel 2
Cloud Point, °C	- 3	- 3
CFPP, °C	- 6	- 5
Distillation, °C		
ASTM D86		
IBP	162	168
20%	206	203
90%	332	330
FBP	375	371
90-20	126	127
FBP-90	43	41

The rapeseed oil methyl ester was produced by extraction from the oilseed by screw pressing, refining, and transesterifying with methanol.

Example 1

In this example, the biofuel used was an RME with a cloud point of -4°C, and a CFPP of -11°C, and the petroleum fuel was Fuel 2.

10 The ethylene-unsaturated ester copolymer was a blend of two ethylene-vinyl acetate copolymers,

EVA 1, 36 wt% vinyl acetate, \overline{M}_n about 2400, CH₃/100 CH₂ 4, and

15 EVA 2, 14 wt% vinyl acetate, \overline{M}_n about 3500, CH₃/100 CH₂ 7.

The weight ratio of EVA 1:EVA 2 was 6:1.

- 21 -

The wax antisetling agent was WASA 1, a blend of equal parts by weight of a C₁₂/C₁₄ alkyl fumarate/vinyl acetate comb copolymer and the amide-amine salt of phthalic anhydride with two molar proportions of hydrogenated tallow.

- 5 320 ppm of the blend of EVA 1 and EVA 2 polymers were mixed with pure RME, pure Fuel 2, and mixtures of RME and Fuel 2, and the CFPP's compared with those of the untreated fuels. The results are shown in Table 1.

10

Table 1

Fuel	CFPP, °C	
	Untreated	Treated
RME alone	- 11	- 13
RME 50%, Fuel 2 50%	- 10	- 27
RME 10%, Fuel 2 90%	- 3	- 27
Fuel 2 alone	- 4	- 16

- 15 From these results it can be seen that while the EVA blend was only marginally effective in RME alone, and showed its usual effect on the CFPP of the petroleum fuel, the CFPP's of the treated RME/Fuel 2 mixtures were substantially reduced.

- 20 Further samples as described above were untreated and treated with, in addition to various concentrations of the EVA blend, various concentrations of WASA 1, and stored at -15°C for 3 days. They were then examined for wax formation, its appearance and degree of settling if present, and the appearance of the liquid. The results are shown in Table 2, together with the CFPP's of the materials.

- 25 In all Tables, the concentration of additives is given in terms of active ingredient actually used.

-22-
Table 2

Conc. EVA, ppm	Conc. WASA, ppm	RME alone	RME/FUEL 50/50	RME/FUEL 10/90	Fuel alone	Sample No
		- CFPP - WAX - FUEL	- CFPP - WAX - FUEL	- CFPP - WAX - FUEL	- CFPP - WAX - FUEL	
0	0	-11 100 SOLID NO LIQ.	-10 NWS CLOUDY	-3 96 FLOCC V.HAZY	-4 NWS CLOUDY	1
320	0	-13 96 SL.HAZY	-27 20 CLOUDY	-27 26 FLUFFY HAZY	-16 25 V.MOB V.HAZY	2
640	0	-13 69 SL. HAZY	-25 20 MOB V. HAZY	-27 54 MOB HAZY	-26 40 V. MOB V.HAZY	3
320	600	-13 85 HAZY	-20 NWS CLOUDY	-17 NWS V.CLOUDY	-19 90 FLUFFY CLEAR	4
640	600	-15 90 MOB V.HAZY	-21 NWS CLOUDY	-18 NWS V.CLOUDY	-21 90 MOB CLOUDY	5
640	1200	-15 90 MOB V.HAZY	-26 NWS CLOUDY	-20 NWS CLOUDY	-16 45 FLUFFY V.HAZY	6

Abbreviation:

NWS - No wax settlement

MOB - MobileWax material described as fluffy was also mobile

V.- Very, SL - Slightly

LIQ. - Liquid

FLOCC - Flocculated

SUBSTITUTE SHEET

- 23 -

The numbers in the "WAX" rows indicate the percentage of the fuel in the vessel occupied by the wax.

5 The results show that the combination of EVA and WASA in fuel mixtures effectively reduces CFPP and prevents wax settlement.

Example 2

In this example, the petroleum-based fuel was FUEL 1; the same RME was used as in Example 1.

10 As well as the blend of EVA 1 and EVA 2 used in Example 1, an ethylene-vinyl acetate copolymer containing 29 weight % vinyl acetate, \overline{M}_n about 2400, $\text{CH}_3/100\text{CH}_2$ 4 was used; this is denominated EVA 3. WASA 2 is a blend of equal parts by weight of a C_{12}

15 alkyl fumarate/vinyl acetate comb polymer and the same amide-amine salt as in WASA 1. WASA 3 is a blend of 1 part each by weight of a C_{16} alkyl polyitaconate and C_{18} alkyl polyitaconate and 2 parts by weight of the same amide-amine salt as in WASA 1.

20 The samples described in Table 3 below were tested for CFPP and for appearance after storage for 4 days at -15°C .

-24-
Table 3

Sample No		7	8	9	10
EVA 1,2,ppm		—	640		
EVA 3,ppm		—		600	500
WASA 1,ppm		—	600	600	
WASA 2,ppm		—			600
WASA 3,ppm		—			
RME alone 1	- CFPP	-13	-15	-15	-13
	- WAX	SOLID	10	20	NWS
	- FUEL	V.CLOUDY	HAZY	HAZY	CLOUDY
RME/FUEL 75/25 1	- CFPP	-11	-17	-14	-16
	- WAX	SOLID	NWS	NWS	NWS
	- FUEL	V.CLOUDY	CLOUDY	CLOUDY	V.CLOUDY
RME/FUEL 10/90 1	- CFPP	-4	-21	-20	-20
	- WAX	NWS	NWS	NWS	NWS
	- FUEL	CLOUDY	CLOUDY	CLOUDY	CLOUDY
RME/FUEL 5/95 1	- CFPP	-6	-20	-18	-12
	- WAX	90 FLOCC	65 FLOCC	45 FLOCC	NWS
	- FUEL	V.HAZY	V.HAZY	CLOUDY	CLOUDY
FUEL alone	- CFPP	-6	-20	-19	-11
	- WAX	85 FLOCC	40	25	2
	- FUEL	V.HAZY	V.HAZY	V.HAZY	CLOUDY

SUBSTITUTE SHEET

2 5

Table 3 cont.

Sample No		11	12	13
EVA 1,2,ppm				640
EVA 3,ppm		600	300	
WASA 1,ppm				
WASA 2,ppm		600		600
WASA 3,ppm			600	
RME alone 1	- CFPP	-14	-14	-13
	- WAX	NWS	50	10
	- FUEL	CLOUDY	HAZY	CLOUDY
RME/FUEL 75/25 1	- CFPP	-16	-22	-15
	- WAX	NWS	NWS	NWS
	- FUEL	CLOUDY	V.CLOUDY	CLOUDY
RME/FUEL 10/90 1	- CFPP	-24	-25	-19
	- WAX	10	NWS	NWS
	- FUEL	CLOUDY	CLOUDY	CLOUDY
RME/FUEL 5/95 1	- CFPP	-13	-21	-12
	- WAX	NWS	53 FLOCC	30
	- FUEL	V.CLOUDY	CLOUDY	V.CLOUDY
FUEL alone	- CFPP	-12	-13	-12
	- WAX	25	32	35
	- FUEL	CLOUDY	CLOUDY	V.HAZY

SUBSTITUTE SHEET

The results in Table 3 show that in many cases the improvement in CFPP and reduction in wax settlement are better for the mixtures than for the individual fuels.

5

Example 3

In this example, Fuel 2 was used, together with the same RME as used in Example 1. The results of Examples 1 and 2 are confirmed. The results are shown in Table 4.

10

27

Table 4

Sample No		14	15	16	17	18
EVA 1,2,ppm		0	320			640
EVA 3,ppm		0		300	600	
WASA 1,ppm		0				1200
WASA 2,ppm		0		600		
WASA 3,ppm		0			600	
RME alone 1	- CFPP	-13	-13	-13	14	-15
	- WAX	SOLID	96	NWS	60	9
	- LIQUID		HAZY	CLOUDY	HAZY	HAZY
RME/FUEL 75/25 1	- CFPP	-15		-16	-12	
	- WAX	NWS		NWS	NWS	
	- FUEL			CLOUDY	CLOUDY	
RME/FUEL 50/50 1	- CFPP	-6	-27	-22	-17	-26
	- WAX	NWS	20	NWS	NWS	NWS
	- FUEL		CLOUDY	CLOUDY	CLOUDY	CLOUDY
RME/FUEL 10/90 1	- CFPP	-5	-27	-28	-27	-20
	- WAX	50	26	NWS	NWS	NWS
	- FUEL	HAZY	HAZY	CLOUDY	CLOUDY	CLOUDY
RME FUEL 5/95 1	- CFPP	-3		-27	-28	
	- WAX	5		2	NWS	
	- FUEL	HAZY		CLOUDY	CLOUDY	
FUEL alone	- CFPP	-5	-16	-12	-14	-16
	- WAX	NWS	25	90	80	45
	- FUEL		HAZY	HAZY	HAZY	HAZY

SUBSTITUTE SHEET

Example 4

In this example, the biofuel used was the same as in Example 1, and the petroleum fuel was Fuel 2.

5 600 ppm of a fumarate-vinyl acetate comb copolymer were mixed with pure RME, pure Fuel 2, and mixtures of RME and Fuel 2, and the CFPP's compared with those of untreated fuels. The copolymer was of a mixed C₁₂/C₁₄ alkyl fumarate obtained by reaction of
10 a 1:1 weight mixture of normal C₁₂ and C₁₄ alcohols with a fumaric acid and vinyl acetate copolymer, prepared by solution polymerization. The results shown in Table 5 indicate that a comb polymer alone is surprisingly effective in reducing the CFPP of a
15 mixture of petroleum and biofuels.

Table 5


Fuel	CFPP, °C	
	Untreated	Treated
RME alone	-11	-10
RME - 50%, Fuel 2 - 50%	-10	-14
RME - 10%, Fuel 2 - 90%	-3	-12
Fuel 2 alone	-4	-8

CLAIMS:

1. A fuel oil composition comprising a biofuel, a petroleum-based fuel oil, and an additive comprising at least one petroleum fuel oil wax crystal modifier or pour point depressant or both, comprising
5 (a) an oil-soluble copolymer of ethylene or, (b) a comb polymer or, (c) a polar nitrogen compound, or (d) a compound in which at least one substantially linear alkyl group having 10 to 30 carbon atoms is connected
10 to a non-polymeric organic residue to provide at least one linear chain of atoms that includes the carbon atoms of said alkyl groups and one or more non-terminal oxygen atoms, or (e) one or more of components (a), (b), (c) and (d).
- 15 2. A composition as claimed in claim 1, wherein the biofuel is a vegetable oil or a re-esterified vegetable oil.
3. A composition as claimed in claim 2, wherein the biofuel is, or is derived from, rapeseed
20 oil.
4. A composition as claimed in claim 2, wherein the biofuel is rapeseed methyl ester.
5. A composition as claimed in any one of claims 1 to 4, wherein the petroleum-based fuel is a
25 middle distillate fraction.
6. A composition as claimed in any one of claims 1 to 5, wherein the petroleum-based fuel is a diesel fuel.
7. A composition as claimed in any one of
30 claims 1 to 6, wherein the biofuel represents from 5 to 75% by weight of the fuel composition.
8. A composition as claimed in any one of claims 1 to 7 wherein component (a) is present and is
35 an oil-soluble copolymer of ethylene with an ethylenically unsaturated ester.

9. A composition as claimed in claim 7, wherein component (a) is a copolymer of ethylene and the ester of an unsaturated alcohol and a saturated carboxylic acid.

5 10. A composition as claimed in any one of claims 1 to 9 wherein component (a) is present and comprises an ethylene copolymer having, in addition to units derived from ethylene, units of the formula



10 wherein R represents H or CH₃, and R³⁰ represents a group of the formula COOR³ or OOCR⁴, wherein R³ and R⁴ independently represent a hydrocarbyl group.

11. A composition as claimed in any one of claims 1 to 10, wherein component (a) is present and comprises two ethylene-unsaturated copolymers, the second having a higher molecular weight and a lower ester content than the first.

12. A composition as claimed in claim 11, wherein component (a) is present and comprises:

20 (i) an oil-soluble ethylene copolymer having, in addition to units derived from ethylene, from 7.5 to 35 molar per cent of units of the formula



and

25 (ii) an oil-soluble ethylene copolymer having, in addition to units derived from ethylene, up to 10 molar per cent of units of the formula




30 wherein each R independently represents H or CH₃, and each R¹ and R² independently represents a group of the formula COOR³ or OOCR⁴, wherein R³ and R⁴ independently represent a hydrocarbyl group, the proportion of units I in polymer (i) being at least 2 molar per cent greater than the proportion of units II in polymer (ii).

35

13. A composition as claimed in any one of claims 1 to 12, which contains the additive in a total proportion of from 0.0005 to 1%, based on the weight of oil.

5 14. A composition as claimed in any one of claims 1 to 13, wherein component (b) is present and is of the general formula



10

wherein

D = R, COOR¹¹, OCOR, R¹²COOR¹¹, or OR¹¹,

E = H, CH₃, D, or R¹²,

G = H or D

15 J = H, R¹², R¹²COOR¹¹, or an aryl or heterocyclic group,

K = H, COOR², OCOR¹², or¹², or COOH,

L = H, R², COOR², OCOR², COOH, or aryl,

R¹¹ ≥ C₁₀ hydrocarbyl,

20 R¹² ≥ C₁ hydrocarbyl,

and m and n represent mole ratios, m being within the range of from 1.0 to 0.4, n being in the range of from 0 to 0.6.

25 15. A composition as claimed in claim 22 or claim 23, wherein the comb polymer is a copolymer of vinyl acetate and a fumarate ester.

16. A composition as claimed in claim 24, wherein the ester groups are alkyl groups having from 12 to 20 carbon atoms.

17. A composition as claimed in claim 25, wherein the ester groups are derived from an alcohol having 12 carbon atoms, or a mixture of alcohols having 12 and 14 carbon atoms.

5 18. An additive concentrate comprising an additive as defined in any one of claims 1 to 17, in a biofuel or in a mixture of a biofuel and a petroleum-based fuel oil.

10 19. The use of an additive as defined in any one of claims 1 to 17 to improve the low temperature properties of a fuel mixture comprising a biofuel and a petroleum-based fuel oil.

INTERNATIONAL SEARCH REPORT

Int. Application No

PCT/EP 93/02908

A. CLASSIFICATION OF SUBJECT MATTER
IPC 5 C10L1/02 C10L1/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 5 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	WO,A,93 18115 (EXXON) 16 September 1993 see page 6, line 24 - line 27; example 1 ---	1-19
Y	FR,A,2 492 402 (I.F.P.) 23 April 1982 see page 5, line 23 - line 28; claims 1-15 ---	1-19
Y	US,A,3 961 916 (ILNYCKYJ ET AL.) 8 June 1976 cited in the application see the whole document ---	1-13,18, 19
Y	EP,A,0 153 177 (EXXON) 28 August 1985 cited in the application see the whole document ---	1-7, 14-19
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

23 February 1994

Date of mailing of the international search report

08.03.94

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

De La Morinerie, B

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 93/02908

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP,A,0 476 197 (ETHYL) 25 March 1992	1-3, 5-10, 18, 19
Y	see page 9, line 41 - line 53 see page 11, line 28 - line 29 ---	4
Y	WO,A,92 11345 (HENKEL) 9 July 1992 see the whole document -----	1-8, 10, 18, 19

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 93/02908

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9318115	16-09-93	NONE	
FR-A-2492402	23-04-82	NONE	
US-A-3961916	08-06-76	NONE	
EP-A-0153177	28-08-85	AU-B- 586968	03-08-89
		AU-A- 3900885	05-09-85
		AU-B- 571309	14-04-88
		AU-A- 3900985	05-09-85
		CA-A- 1278683	08-01-91
		CA-A- 1282240	02-04-91
		DE-A- 3584574	12-12-91
		DE-A- 3584729	09-01-92
		EP-A, B 0153176	28-08-85
		JP-A- 60195192	03-10-85
		JP-B- 4073473	20-11-92
		JP-A- 60195193	03-10-85
		US-A- 4810260	07-03-89
		US-A- 4713088	15-12-87
		US-A- 4863486	05-09-89
EP-A-0476197	25-03-92	AU-B- 634422	18-02-93
		AU-A- 8465391	26-03-92
		CA-A- 2051451	21-03-92
		JP-A- 4234490	24-08-92
WO-A-9211345	09-07-92	DE-A- 4040317	25-06-92
		EP-A- 0563070	06-10-93

THIS PAGE BLANK